





## Realtime RS-70

### Specifications


» Fingerprint Users	5,000
» Card User	5,000
» Password User	5,000
» Attendance Records	100,000
» CPU	32bit CPU
» Fingerprint sensor	Optical sensor 500DPI
» Interlocking detection	Support (With Magnetic Contact)
» Multi-device Related	Max. 255units
» Card reader	RF ID card reader (Option: Mifare reader/HID Reader)
» Display	2.0 inch TFT display
» LED	Two(Red, Blue)
» TouchPad	16Keys (Touch)
» Communication	TCP/IP, USB, RS485
» USB disk	Support
» Additional function	Tamper Detection
» Working voltage	DC 12V ± 10%
» Working humidity(RH)	20 % - 80 %
» Working temperature	-10°C ~ +50°C
» Alarm function	Support tamper, long time door open, illegal door open and intimidate alarm.
» Power management	Support sleep mode
» Self-test function	Support
» FAR/ FRR	0.00001/ 0.1(%)
» Fingerprint input angle	360°(any angle)
» Intelligent adaptation function	Support
» Matching mode	Support 1:N, 1:1




Auto-Adapt  
Sensor




Auto-Push  
Technology




Cloud  
Technology




Slave RF Reader  
Connectivity




Fingerprint  
Scanner




PIN  
Personal  
Identity Number




EM Card




USB Link




USB Disk



Access  
Control



TCP/IP



RS232/485